

**SP6—ADVANCED SERIES 6-OUTLET SURGE PROTECTOR**



**Features**

- Six switched AC power outlets
- Diagnostic indicator lights (4)
- Six switched AC power outlets
- Diagnostic indicator lights (two)
- Eight foot power cord with right angle plug
- EMI/RFI noise filtration
- Integrated cable management
- **Lifetime Product Warranty**—This surge protector shall be free of any defects in design, materials, or workmanship, or ITW Linx will repair or replace the defective product.

**Technical Specifications**

*Designs and specifications are subject to change without notice due to product improvement.*

**PRODUCT SPECIFICATIONS:**

Agency Approval	UL 1363, 1449
LED Indicators	2
Grounding Requirements	Uses Electrical AC Ground
Ground Impedance	N/A
Width	4.6"
Height	12.5"
Depth	2.9"
Weight	2.18 lbs
Product Warranty	Lifetime
Connected Equipment Warranty	N/A

**SIGNAL LINE SURGE PROTECTION:**

**TELCO CIRCUIT PROTECTION**

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resettable	N/A
Clamping Level	N/A
Response Time	N/A
Capacitance	N/A
Suppression Modes	N/A
Wires Protected	N/A
Termination Type	N/A

**COAX CIRCUIT PROTECTION**

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resettable	N/A
Response Time	N/A
Termination	N/A
Antenna/Cable Lines Protected	N/A
Antenna/Cable Clamping Level	N/A
Antenna/Cable Attenuation	N/A
Satellite Lines Protected	N/A
Satellite Clamping Level	N/A
Satellite Attenuation	N/A

**LAN CIRCUIT PROTECTION**

Signal Perfect Circuitry	N/A
Fuseless/Auto-Resettable	N/A
Performance Rating	N/A
Clamping Level	N/A
Response Time	N/A
Wires Protected	N/A
Termination Type	N/A

For up-to-date warranty information see our web site: [www.itwlinx.com](http://www.itwlinx.com)



**AC SURGE PROTECTION:**

SurgeGate Plus Circuitry	N/A
Thermal Fusing	Yes
Catastrophic Surge Circuit	Yes
Over/Undervoltage Voltage Protection	N/A
Overvoltage Voltage Shutoff	N/A
Undervoltage Voltage Shutoff	N/A
Single Pulse Energy Dissipation	1020 Joules
Peak Impulse Current	48,000 A
EMI/RFI Noise Filtration	50db (99.97%)
Line Voltage	120V (50/60Hz)
Initial Clamping Level	200V Peak, 141 Rms
UL 1449 Rating	330V
Protection Modes	L-N, L-G, N-G
Maximum Current Rating	15A (1800W)
Response Time	1-5 Nanoseconds
Plug Configuration	Right Angle
Number of Outlets	6
Switched Outlets	6
Cord Length	8'

**Ordering Information**

ITW Linx Part Number	Description
<b>SP6</b>	6-outlet AC surge protector, with Protect or Disconnect circuitry and integrated cable management.

**Applications:**

- Telephone Systems
- Workstations
- Printers
- Fax Machines
- Copiers
- TVs / VCRs
- Cameras
- Access Controls
- Alarms